

COMMERCIAL & INDUSTRIAL INDOOR LUMINAIRE

LED Linear High Bay

Illuminate indoors areas day and night with DuraGem™ Technology. Engineered for balanced LED lumen output with long-rated life. Smart Ready for photocell, daylight, and bi-level dimming, and occupancy sensor functions.

Features

Sizes	2 ft and 4 ft
Finish	Pure White Semi-Gloss
Diffuser	Anti-UV Frosted Polycarbonate Lens
Rated Life	75000 hours
Warranty	7 years

Construction

Manufactured for durability using heavy duty die cast aluminum housing with anti-UV polyester coating to resist corrosion, discoloration, and scratching.

Applications

Primary use as high-bay luminaires for commercial and industrial buildings. Pendant or surface mounted specifically for indoor high ceiling spaces above 25 feet.

Listings

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant. View DLC Premium listing at: designlights.org/qpl

Warranty

7 year exclusive limited warranty. View complete product warranty information at: etheriumled.com/warranty



Project:
Date:
Catalog No:
Prepared By:



Performance

Wattage	See ordering information.
Voltage	120-277V
Frequency	50/60 Hz
Efficacy	130 lm/W
CCT	4000K or 5000K
CRI	≥ 80
Power Factor	≥ 0.9
THD	≤ 15%
Operating Temp.	-20°C to 50°C (-4°F to 122°F)
Dimming	0-10V

ORDERING INFORMATION

Model No.	Wattage (W)	Voltage (V)	CCT (K)	Light Output	Efficacy (lm/w)	Rated Life
AL-HBE-2-90W-4K	90	120-277V	4000K	11700 lm	130 lm/W	75000 hrs
AL-HBE-2-90W-5K	90	120-277V	5000K	11700 lm	130 lm/W	75000 hrs
AL-HBE-2-110W-4K	110	120-277V	4000K	14300 lm	130 lm/W	75000 hrs
AL-HBE-2-110W-5K	110	120-277V	5000K	14300 lm	130 lm/W	75000 hrs
AL-HBE-2-162W-4K	162	120-277V	4000K	21060 lm	130 lm/W	75000 hrs
AL-HBE-2-162W-5K	162	120-277V	5000K	21060 lm	130 lm/W	75000 hrs
AL-HBE-4-225W-4K	225	120-277V	4000K	29250 lm	130 lm/W	75000 hrs
AL-HBE-4-225W-5K	225	120-277V	5000K	29250 lm	130 lm/W	75000 hrs
AL-HBE-4-321W-4K	321	120-277V	4000K	41730 lm	130 lm/W	75000 hrs
AL-HBE-4-321W-5K	321	120-277V	5000K	41730 lm	130 lm/W	75000 hrs

DIMENSIONS: 23.80"L x 12.60"W x 3.62"H