



AL-LSB-400W

LED AREA LIGHT

SHOE BOX SERIES



GENERAL DESCRIPTION

Our Area Light/Shoebox Series is the best option to replace 100W to 1000W metal halide luminaires. The slim profile design delivers maximum efficiency. A wide range of lumen packages for any type of applications. With extensive selection of accessories, including photocell receptacles, motion sensor, mountings and finish colors.

Ideal for commercial parking lots, car dealership, walk ways, street lighting, and places where much needed light.

FEATURES

- Lumileds LED, high luminous efficiency and long working life.
- High efficiency LED Driver, the wide range input voltage AC120-277V/AC 277-480V.
- Die-cast aluminum cooling design, high quality and better cooling for LED Tj < 85°C.
- Excellent optics design, greatly improve the light utilization and evenness.
- Motion sensor control available (Optional)



ORDERING INFORMATION

AL	LSB	400W	27	50K	Z	TN	U	Y	#
COMPANY	PRODUCT	WATTAGE	VOLTAGE	CCT	FINISH	DISTRIBUTION	MOUNTING	CONTROL 1	CONTROL 2
AL	LSB (Shoebox)	400W - (400W)	27 (AC120-277V) 48 (AC277-480V)	40K - (4000K) 50K - (5000K)	D - (Dark Bronze) W - (White) B - (Black) S - (Silver)	T2 - (Type II) T3 - (Type III) T4 - (Type IV) T5 - (Type V)	S - (Slipfitter) A - (Arm) T - (Trunnion)	P - (Photocell)	M - (Motion Sensor) RC - (Remote Controller)

ELECTRICAL LOAD

WATTAGE	CURRENT (VOLTAGE) (AMP)					
	120V	208V	240V	277V	347V	480V
	3.33 Amp	1.92 Amp	1.66 Amp	1.44 Amp	1.15 Amp	0.83 Amp




AL-LSB-400W

LED AREA LIGHT

SHOE BOX SERIES

DIMENSIONS



A-14.57" x B-25.53" x C-3.16"

	GROSS WEIGHT		23 lbs	BOX DIMENSION		28.74" x 17.32" x 6.1"
CONFIGURATION						
EPA	0.86 ft ²	1.72 ft ²	1.38 ft ²	2.24 ft ²	2.10 ft ²	2.76 ft ²
NET WEIGHT	21.4 lbs	42.8 lbs	42.8 lbs	64.2 lbs	64.2 lbs	85.6 lbs

SPECIFICATION

WATTAGE	400W
LUMEN	56783 lm
EFFICACY	141 lm/W
CCT	4000K, 5000K
CRI	70
INPUT VOLTAGE	AC120-277V / AC277-480V
DISTRIBUTION	Type II, Type III, Type IV, Type V
POWER FACTOR	0.95
DRIVER EFFICACY	90%
DIMMING	0-10Vdc
LIFE SPAN	over 50,000 hrs
WORKING TEMPERATURE	-22°F ~ 113°F
STORAGE TEMPERATURE	-40°F ~ 176°F
OUTDOOR RATING	Wet location / IP65
CABLE	3 core, 18AWG 0.5m
WARRANTY	5 year limited

CONTROLS (SOLD SEPARATELY)



P
Photocell



M
Motion Sensor



RC
Remote Controller



GATEWAY

MOUNTING OPTIONS



NEWSBSF2-D Slipfitter
Mount An optional cast aluminum mast arm adapter secures fixture head to nominal 2"(2-3/8" O.D. pipe size) horizontal steel tenon arm.



NEWSBARM2-D
Arm Mount 4" and 5" Square and Round poles. Standard versatile mounting arm is simple to install and can be used with existing poles for retro installations.



SFARM2-D SFARM2
Mount An optional cast aluminum mast arm adapter secures fixture head to nominal 2"(2-3/8" O.D. pipe size) horizontal steel tenon arm.



SBT-D
Easy to install for direct wall mounting with 1/2" conduit wiring.



SADP-BAR-D Square
tube light bar installation, with Arm installation of lamps.






ARM-BAR-D Square
tube light bar installation, with Arm installation of lamps.

DISTRIBUTION

TYPE II

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM






TYPE II

Type II optics produce a symmetrical pattern that evenly shines light on both sides of the lamp. In a back-to-back configuration, it creates a rectangular pattern.

TYPE III

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM






TYPE III

Type III optics produce an asymmetrical pattern that directs the majority of the light forward and equally on both sides of the luminaire. In a back-to-back configuration, it creates a rectangular pattern.

TYPE IV

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM






TYPE IV

Type IV is suitable for applications where light is primarily required forward with minimal backlight. Typical installations include perimeter poles.

TYPE V

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



TYPE V

Type V optics produce a symmetrical square distribution pattern that distributes light equally on all sides of the luminaire. Type 5 luminaires are universal for most area lighting applications.