

## Selectable LED Semi-Cutoff Wall Pack + Photocell

3-Wattages + 3-CCT (30/40/50K), Wet Rated, 130 lm/W, Dimmable + Photocell + Smart

### FEATURES

<b>Lumen Output</b>	5850 to 15600
<b>Wattage</b>	3-WATT (80W Max, 120W Max)
<b>Efficacy</b>	130 lm/W
<b>Input Voltage</b>	120-277 or 480 Volt
<b>Dimmable</b>	0-10V Continuous
<b>CCT</b>	Select (3000K, 4000K, 5000K)
<b>Color</b>	Bronze
<b>Rating</b>	Wet Location
<b>Warranty</b>	5 Years

### APPLICATIONS

Premium outdoor luminaire suitable for wall mounting on building exteriors for entrances, courtyards, alleys, and pedestrian walkways.

### CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

### ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3000K, 4000K, 5000K) and Tunable 3-Wattages. Operating temperatures -4°F to 113°F (-20°C to 45°C).

### MOUNTING

Wall mounted installations. Includes Liquid Level inside housing.

### OPTICS

Anti-UV Prismatic Tempered Glass Lens, or Anti-UV Prismatic Polycarbonate Lens available.

### CONTROLS

Installed fixture integrated Photocell sensor.

### EMERGENCY

Installed 90 Minute Emergency Backup Battery LED Driver available.

### LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

### WARRANTY

5 year exclusive limited warranty.

Project:
Date:
Catalog No:
Prepared By:

Tunable 80W Max and 120W Max Models with Photocell



\*Includes Liquid Level and Silicone Water Repellent Ring



Emergency Driver




### TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3000K

4000K

5000K



SPECIFICATIONS

ENERGY DATA

**Input Voltage:** 120-277 or 480 Volt  
**Input Frequency:** 50/60 Hz  
**Wattage:** 3-Wattages (80W Max, 120W Max)  
**Power Factor:** >0.9  
**Total Harmonic Distortion (THD):** <15%  
**Operating Temperature:** -4°F to 113°F (-20°C to 45°C)

LIGHTING DATA

**Lumens:** 5850 to 15600  
**Lumens Per Watt:** 130 lm/W  
**Correlated Color Temperature (CCT):** 3-CCT (30K, 40K, 50K)  
**Dimmable:** 0-10V  
**Color Rendering Index (CRI):** >70  
**L70:** 50000 hours

ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
AL-QWP-80W-CCT-PC *Glass Lens	45W 60W 80W	120-277V	0.41A@120V, 0.18A@277V 0.55A@120V, 0.24A@277V 0.73A@120V, 0.32A@277V	5850 7800 10400	130 lm/W	(3000K, 4000K, 5000K)	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D
AL-QWP-80W-CCT-PC *PC Lens	45W 60W 80W	120-277V	0.41A@120V, 0.18A@277V 0.55A@120V, 0.24A@277V 0.73A@120V, 0.32A@277V	5850 7800 10400	130 lm/W	(3000K, 4000K, 5000K)	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D
AL-QWP-120W-CCT-PC *Glass Lens	90W 100W 120W	120-277V	0.83A@120V, 0.36A@277V 0.92A@120V, 0.40A@277V 1.10A@120V, 0.48A@277V	11700 13000 15600	130 lm/W	(3000K, 4000K, 5000K)	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D
AL-QWP-120W-CCT-PC *PC Lens	90W 100W 120W	120-277V	0.83A@120V, 0.36A@277V 0.92A@120V, 0.40A@277V 1.10A@120V, 0.48A@277V	11700 13000 15600	130 lm/W	(3000K, 4000K, 5000K)	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D

Control

**SD250** [INSTALLED] Step-Down Autotransformer 480V to 277V, Up To 250W

Emergency

**EM20 (BLD-CM20H-YYY)** [INSTALLED] Emergency Backup LED Driver, 20W, 90-Min Battery

PHYSICAL DIMENSIONS

All Models

14.21"L x 9.27"W x 7.31"D

