



ACCESSORIES OPTIONS:



PHOTOCELL



MOTION SENSOR

FEATURES

- Designed for installing new construction or retrofitting existing commercial building
- Four different bracket designs for multiple mounting options
- ip66 rated fixture with outstanding corrosion protection
- Rugged die-cast aluminum housing
- DLC premium
- Surge Protection
- 5.0 Parking Lot Led

ELECTRIC CHARACTERISTIC

350W - 300W - 250W

INPUT VOLTAGE	110 - 277 VAC / 480 VAC
CRI	>70
LUMEN PER WATT	250W - 140 LM/W 300W - 146 LM/W 350W - 146 LM/W
AVAILABLE CCT	4000K, 5000K
LIFE SPAN	50,000 HOURS
OPERATION TEMPERATURE	-40°F ~ 113°F
LUMEN	250W - 35,000 LM 300W - 42,000 LM 350W - 51,100 LM
MOUNTING OPTIONS	DIRECT ARM MOUNT, SLIP FITTER, TRUNNION MOUNT, WALL MOUNT
BEAM ANGLE	DUE TO OPTICAL TYPE

200W - 150W - 100W

INPUT VOLTAGE	110 - 277 VAC / 480 VAC
CRI	>70
LUMEN PER WATT	146 LM/W
AVAILABLE CCT	4000K, 5000K
LIFE SPAN	50,000 HOURS
OPERATION TEMPERATURE	-40°F ~ 113°F
LUMEN	100W - 14,600 150W - 21,000 LM 200W - 27,000 LM
MOUNTING OPTIONS	DIRECT ARM MOUNT, SLIP FITTER, TRUNNION MOUNT, WALL MOUNT
BEAM ANGLE	DUE TO OPTICAL TYPE

LIGHTING UP THE WORLD
WITH ONE BULB AT A TIME!

ORDERING INFORMATION

350W- 300W - 250W


AL-LEDTPK	300W	50K	[BLANK]	[BLANK]	3	[BLANK]	-SP
SERIES AL-LEDTPK	RATED WATTAGE 350W 350 WATT 300W 300 WATT 250W 250 WATT	COLOR TEMP 40K 4000 KELVIN 50K 5000 KELVIN	FINISHING BLANK DARK BRONZE BK BLACK WH WHITE SG SILVER GRAY	INPUT VOLTAGE BLANK 110 - 277 VAC HV 480 VAC	DISTRIBUTION TYPE 3 TYPE III 5 TYPE V	CONTROL ACCESSORY BLANK -NO ACCESSORY -PC TWIST LOCK PHOTOCELL -MS MOTION SENSOR	MOUNT SP -SLIPFITTER AM -DIRECT ARM MOUNT WM -WALL MOUNT TM -TRUNNION MOUNT

200W - 150W - 100W


AL-LEDTPK	200W	50K	[BLANK]	[BLANK]	3	[BLANK]	-SP
SERIES AL-LEDTPK	RATED WATTAGE 200W 200 WATT 150W 150 WATT 100W 100 WATT	COLOR TEMP 40K 4000 KELVIN 50K 5000 KELVIN	FINISHING BLANK DARK BRONZE BK BLACK WH WHITE SG SILVER GRAY	INPUT VOLTAGE BLANK 110 - 277 VAC HV 480 VAC	DISTRIBUTION TYPE 3 TYPE III 5 TYPE V	CONTROL ACCESSORY BLANK -NO ACCESSORY -PC TWIST LOCK PHOTOCELL -MS MOTION SENSOR	MOUNT SP -SLIPFITTER AM -DIRECT ARM MOUNT WM -WALL MOUNT TM -TRUNNION MOUNT

DIMENSIONS

200W - 150W - 100W



350W - 300W - 250W




LIGHTING UP THE WORLD
WITH ONE BULB AT A TIME!

LIGHT DISTRIBUTION TYPE


Type 3:

Type 3 optics produce an asymmetrical pattern that directs the majority of the light forward and equally on both sides of the luminaire. In a back-to-back configuration, it creates a rectangular pattern which can extend pole spacings.




Type 4:

Type 4 is suitable for applications where light is primarily required forward with minimal backlight. Typical installations include perimeter poles.



Type 5:

Type 5 optics produce a symmetrical square distribution pattern that distributes light equally on all sides of the luminaire. Type 5 luminaires is universal for most area lighting applications.



OPTIONAL ACCESSORIES

Housing

Features a compact, one-piece die cast housing, saving costs versus models that are extruded or cast and require additional parts. The heat sink is included in the actual casting, further minimizing

PHOTOMETRY








Optional Type III or type IV or type V
Photometry as per applications.



Standard Arm Mount





The design features an integral arm, increasing strength and simplifying installation.

EPA OF AREA LIGHT

ITEM							
	1	2 @ 90°	2 @ 120°	2 @ 180°	3 @ 90°	3 @ 120°	4 @ 90°
100W/150W/200W	0.4418	0.7145	0.8813	0.8836	1.0548	1.0135	1.0548
250W/300W/350W	0.5614	0.8471	1.105	1.1228	1.294	1.2503	1.294

LIGHTING UP THE WORLD
WITH ONE BULB AT A TIME!

ACCESSORY LIST

Mounting Type	Accessory	Specifications	Quantity
 Slipfitter Mount	Slipfitter	Adjustable slipfitter	1
 Square mount	① Pole Mount Arm	19.9 x 17.7 x 9cm Square pole mount arm	1
	② Bolt	# 1/2" x 1.97" Stainless Steel Hexagon Hexagon head bolt	2
 Round mount	① Pole Mount Arm	19.9 x 17.7 x 9cm Square pole mount arm	1
	② Bolt	# 1/2" x 1.97" Stainless Steel Hexagon Hexagon head bolt	2
	③ Adaptor	17.7 x 8.8 x 1.3cm Round pole adaptor	1
 Wall mount	① Pole Mount Arm	19.9 x 17.7 x 9cm Square pole mount arm	1
	② Wall Mount Plate	20.3 x 15.2 x 0.5cm Steel Plate	1
	③ Wall Mount Template	20.3 x 15.2 x 0.1cm Aluminum alloy plate	1
	④ Bolt	KM4 x 10" Stainless Steel flat head bolt	4
	⑤ Bolt	# 1/2" x 1.46" Stainless Steel Hexagon head bolt	2
Others	Twist-lock photocell	120-277V 3-Pin	1
	Receptacle	3-Pin receptacle	1
	Bolt	PM4 x 8 Stainless Steel, Round Flat bottom Bolt	2
	Occupancy Sensor	120-277V 0-10V Bi-level	1

MOUNTING OPTIONS



SLIPFITTER MOUNT (-SP)



ARM MOUNT (-AM)



TRUNNION MOUNT (-TM)



WALL MOUNT (-WM)



TRUNNION MOUNT (-TM)
(FOR 250W - 300W)

LIGHTING UP THE WORLD
WITH ONE BULB AT A TIME!