


Product Specification

Product code(s): GPRE02BSU-TR							
Description: Decorator Duplex USB charger.							
Performance Requirements: Contains the required Supervisory Circuit with the Auto-Monitoring Function as noted by UL 1310							
Parameter	Symbol	Condition	Min.	Nom.	Max.	Comments	Unit
Input Voltage	VAC		112	125	137		VAC
Frequency	Hz		\	60	\		Hz
Front Receptacle Current	AC	150 VAC Nominal	\	20	\		A
USB Output current	DC	5 VDC Nominal	\	3.1	\		A
Mechanical Requirements							
Parameter	Symbol	Scholium	Min.	Nom.	Max.	Comments	Unit单位
Length	L	\		104.0		\	mm
Width	W	\		42.0		\	mm
Height	H	\		47.7		\	mm
Material Requirements							
Part	Quantity (pcs)	Material/Description					
Front receptacle (enclosure) color	1	White					
Back enclosure color	1	Black					
Front Cover	1	R/C Plastics, Lexan 241R (Sabic Innovative Plastics - E207780)					
Mounting Yoke	1	Nickel or Zinc plated steel, 1.02 mm thick					
Grounding Terminal	1	Plated steel					
Fastening Screw	4	Nickel plated steel					
Wire Braid (line)	1	Copper braided wire					
Neutral wire Screw	1	Nickel plated steel					
Printed Wiring Board	1	R/C PWB (ZPMV2), FR-4, 94-V0, rated 130 °C.					
Application Requirements							
Item	Specification						
Accepted Terminal Wire Size	12 gauge						
Wiring Type	Rear pressure plate and side wiring						
Flammability	5Va						
Operating Temperature	-35 to 66 Celsius						
Operating Humidity	30-95%						
Product Marking Requirements							
Parameter	Description or Reference Document						
UL Marking and Labels.	Labels and markings as required by UL file # E305815.						