

Product Specification

Product code(s): LUXDM600-02-3

Description: Dimmer INC 600W、LED150W、CFL150W

Performance Requirements: UL 20.



Parameter	Symbol	Condition	Min.	Nom.	Max.	Comments	Unit
Input Voltage	VAC		\	120	\		VAC
Frequency	Hz		\	60	\		Hz
Front Receptacle Current	IAC	120 VAC Nominal	\	5	\		A

Mechanical Requirements

Parameter	Symbol	Scholium	Min.	Nom.	Max.	Comments	Unit
Length	L	\		104.6		\	mm
Width	W	\		56.1		\	mm
Height	H	\		49.63		\	mm
Weight	WT	\		86.18		\	g

Material Requirements

Part	Quantity (pcs)	Material/Description	
推杆帽	1	atics, PC 241R(Sabic Innovative Plastics - E207780)	
Front Cover	1	R/C Platics, PC 241R(Sabic Innovative Plastics - E207780)	
船型开关	1	KCD5-2P-32 125V/10A	
Mounting Yoke	1	aluminium, 1.6mm .	
PCB		1.6mm, 94V-0	
Grounding Terminal	1	Green Wire, the shortest 6 inch	
电源导线	3	Red wire and black wire,the shortest 4 inch	
back Cover	1	R/C Platics, PC 241R(Sabic Innovative Plastics - E207780)	

Application Requirements

Item	Specification
UL1472	
导线规格	18#
Flammability	Rated V-2 per UL 94

Product Marking Requirements

Parameter	Description or Reference Document
UL Marking and Labels.	UL file # E250099
GP brand markings	\